

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 10-322362

(43)Date of publication of application : 04.12.1998

(51)Int.Cl. H04L 12/28
H04B 3/46
H04B 10/08
H04B 10/105
H04B 10/10
H04B 10/22

(21)Application number : 10-022942

(71)Applicant : DIGITAL EQUIP CORP <DEC>

(22)Date of filing : 04.02.1998

(72)Inventor : FLAHERTY PAUL A

(30)Priority

Priority number : 97 794509 Priority date : 04.02.1997 Priority country : US

(54) COMMUNICATION METHOD/DEVICE WITH DETECTION OF COMMUNICATION COLLISION

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a collision detection method for highly using infrared band width which the multiplex access infrared (LAN can use by detecting the energy level of the electromagnetic wave of a second wavelength while first datum is transmitted through the use of a first wavelength and declaring collision when the energy level of the second wavelength exceeds a threshold.

SOLUTION: A duplex wavelength infrared transceiver 101 transmits a signal 361 in wavelength bands $\lambda 1$ and $\lambda 2$ and a transceiver 102 starts transmitting a signal 362 in the wavelength bands $\lambda 1$ and $\lambda 2$. The duplex wavelength receiver 141 of the transceiver 101 receives the synthesized signal of the signals 361 and 362 in the wavelength bands $\lambda 1$ and $\lambda 2$. When a duplex wavelength transmitter 121 does not transmit the signal 361 in the wavelength bands $\lambda 1$ and $\lambda 2$, collision is declared at the time of detecting the synthesized signal of the energy level larger than the prescribed threshold for, the corresponding wavelength. Thus, collision is accurately detected.

